

# Key Product Highlights

## KEY PRODUCT HIGHLIGHTS

### FAX-L170



- **Accompanying HANDSET**
- **Compact design and small footprint**
- **Print Speed Up to 18/19ppm (A4/Letter)**
- Print Resolution: Up to 600x600dpi; 1200 (equivalent)x600dpi with Image Refinement Technology
- Copy Speed: 11.8cpm/12.4cpm (A4/Letter)
- First printout Time (FPOT): 7.8 secs or less
- Warm Up Time from power-on: 14 secs or less
- **Recovery time from Deep Sleep: 3.5 secs or less**
- UFR II LT Print Language
- Fax Modem: 33.6Kbps
- **30-sheet Auto Document Feeder**
- Fax Reception Memory: 512 pages
- **5-line LCD display**
- 150-sheets fold-in paper cassette
- 64 MB RAM
- **Energy Saving: 1.5W (Sleep Mode)**
- **Energy Star TEC: 0.6kWh/W**
- All-in-one Cartridge 328 (2,100 pages; bundled cartridge: 1,000 pages)

5

# Product Specifications

# Product Specifications

PRINT		FAX-L170
Printing Method	Monochrome Laser	
Print Speed (A4/Letter)	18/19ppm	
Print Resolution	Up to 600 x 600dpi 1200 (equivalent) x 600dpi	
Warm-up Time (From Power On)	14 secs or less	
First Printout Time (FPOT)	Approx. 7.8 secs (A4), 7.7 secs (LTR)	
Recovery Time (From Sleep Mode)	Approx. 3.5 secs.	
Print Language/Emulation	UFR II LT	
Print Margins	top/5 mm, bottom/6mm, left/5mm, right/5 mm (Other sizes than Envelope) 10 mm-top, bottom, left and right (Envelope)	
Print Features	Watermark, Page Composer, Toner Saver	
<b>COPY</b>		
Copy Speed	LTR: 12.4ppm (pages per minute) A4: 11.8ppm (pages per minute)	
Copy Resolution	600 x 600dpi	
First Copy Time (FCOT)	Approx. 22.3 secs (A4), 21.3 secs (LTR)	
Maximum Number of Copies	Up to 99 copies	
Reduce/Enlargement	50 - 200% in 1% increments	
Copy Features	Density Adjustment, Toner Saver	
<b>FAX</b>		
Modem Speed	Up to 33.6Kbps	
Fax Resolution	Up to 200 x 400dpi	
Compression Method	MH, MR, MMR	
Memory Capacity *1	Up to 512 pages	
One-Touch Dial	30 dials	
Speed Dial (One Touch + Coded dials)	Up to 130 dials	
Group dials / Destinations	Max. 129 dials / Max. 129 destinations	
Sequential broadcast	Max. 140 destinations	
Receive Mode	FAX Only, Manual, Answering, Fax/Tel Auto Switch	
Memory Backup	Yes, 5 minutes	
FAX Features	FAX Forwarding, Dual Access, Remote Reception, PC FAX (TX only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports	

# Product Specifications

PAPER HANDLING	
Auto Document Feeder	30 sheets (80g/m <sup>2</sup> or less )
Available Paper Size for ADF	A4, B5, A5, B6, Letter, Legal, Statement, Min. 127 x 139.7mm to Max. 216 x 356mm
Paper Input	Plain Paper (60-80g/m <sup>2</sup> ): 150-sheet cassette
Paper Output	100 sheets (face down)
Paper Sizes	A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, Postcard, Postcard without folding line, Tetrahedral Postcard, Envelope: COM10, Monarch, C5, DL, Custom(Min. 76.2 x 127mm to Max. 216 x 356mm)
Paper Types	Plain, Heavy, Recycled, Transparency, Label, Envelope
Paper Weight	60 to 163g/m <sup>2</sup>
CONNECTIVITY AND SOFTWARE	
Standard Interface(s)	USB 2.0 High Speed
OS Compatibility	Windows 7 (32/64bit* <sup>2</sup> ), Windows Vista (32/64bit* <sup>2</sup> ), Windows XP (32/64bit* <sup>2</sup> )/Windows 2000 Mac® OS X 10.4.9 & up, Linux* <sup>3</sup>
Software Included	Printer Driver, Fax Driver

# Product Specifications

GENERAL SPECIFICATIONS	
Memory	64MB (max.)
LCD Display	5-line BW LCD
Dimensions (W x D x H)	372 x 303 x 303mm (cassette closed) 372 x 400 x 303mm (cassette opened)
Weight	8.2kg (with cartridge) 8.8kg (without cartridge)
Power Consumption	Max: 1020W or less (max.) During Operation: Approx. 400W (in Copying) During Standby: Approx. 10W During Sleep: Approx. 1.5W
TEC (Typical Electricity Consumption)	0.6kWh/W
Noise Levels	Sound pressure Level (Bystander's position) : 53dB in B/W Printing (reference value) Sound Power Level : 6.5B or less in B/W Printing
	Sound pressure Level (Bystander's position) : Inaudible*4 (reference value) Sound Power Level : 4.3B or less
Operating Environment	Temperature: 50 to 86°F (10 to 30°C) Humidity: 20% to 80% RH (no condensation)
Power Requirements	AC 220 to 240V: 50/60Hz
Toner Cartridge*5	Cartridge 328: 2,100 pages (Bundled cartridge: 1,000 pages)
Monthly Duty Cycle*6	Up to 8,000 pages

\*1 Based on ITU-T #1 Chart (standard mode)

\*3 Linux supports printing only

\*4 "Inaudible" means each Sound pressure level at bystander's position is less than the absolute criterion value about background noise of ISO 7779.

\*5 Toner cartridge yield in accordance with ISO/IEC 19752

\*6 Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.